

Philips
PAL coax cable

2 m

> 75 dB Male-Female

SWV2813W



Ensure a reliable connection

with this PAL coax cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

- Nickel-plated connectors for reliable contact

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS
sense and simplicity

PAL coax cable
2 m > 75 dB Male-Female

Specifications

Packaging dimensions

- **Packaging dimensions (W x H x D):**
9.4 x 23.6 x 3.6 cm
- **Nett weight:** 0.110 kg
- **Gross weight:** 0.130 kg
- **Tare weight:** 0.020 kg
- **EAN:** 87 12581 37944 5
- **Number of products included:** 1
- **Packaging type:** Blister

Outer Carton

- **Outer carton (L x W x H):** 33.0 x 25.9 x 17.8 cm
- **Nett weight:** 1.320 kg

- **Gross weight:** 1.860 kg
- **Tare weight:** 0.540 kg
- **EAN:** 87 12581 37946 9
- **Number of consumer packagings:** 12

Inner Carton

- **Inner carton (L x W x H):** 24.4 x 10.4 x 16.0 cm
- **Nett weight:** 0.440 kg
- **Gross weight:** 0.530 kg
- **Tare weight:** 0.090 kg
- **EAN:** 87 12581 37945 2
- **Number of consumer packagings:** 4

SWV2813W/10

Product highlights

Bare copper shielding

Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2008-09-26

Version: 1.0.9

12 NC: 8670 000 35429
EAN: 87 12581 37944 5

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com